


24VDC Power Supply (no relay, 90-480VAC)



SPECIFICATIONS

The Avi-on AVI-PS-480-24-500 power supply is a simple, cost-effective, versatile 24VDC power supply for commercial and industrial lighting applications. Typical applications include individual fixture controls with a dim-to-off driver that does not have an auxiliary power supply and for 24V powered network sensors. The AVI-PS-480-24-500 can accommodate input voltages ranging from 90-480VAC and deliver an output of up to 500mA at 24V DC. It also features screw pads for fixture mounting.

Features

- 24V DC 500mA output
- Class 2, Commercial application rated
- · ETL Recognized

Certifications

- ETL Recognized, Conforms to UL STD. 1310
- CSA STD. C22.2 No. 223
- FCC Part 15

Product Data

- Product Type: Class 2 Power Supply
- Input: 90-480VAC, 47/63Hz, ≤0.5A
- Output: 24VDC, 500mA, 12W
- Over Voltage Protection: ≤1.0A (1A@250VAC Fuse)
- No Load Power Dissipation: ≤0.21W
- Operating Temp: -30°C to 70°C
- Storage Temperature: -40° C to 70°C
- Relative Humidity: 5-95% (non-condensing)
- · Color: White

ORDERING INFORMATION

Part Number	Name	Description
AVI-PS-480-24-500	24VDC Power Supply (no relay, 90-480VAC)	24V Low Voltage Power Supply

To order please contact Avi-on sales at **(877) AVION-US,** (877) 284-6687 or **prosales@avi-on.com** for information on becoming an Avi-on partner and order details.

Project	Location/ Type	



DIAGRAMS




Figure 1. Dimensions



Figure 2. Wiring Diagram

